

Specifications of Anti Scratch High Gloss Acrylic Panels

Attributes	Units	Values
Dimension	mm	19.5
Top Surface		Coextruded engineered acrylic with a proprietary lacquer coating
Core		Russian Birch Plywood
Backer		Shock Resistance Polystyrene
Adhesive		Hotmelt PUR
Gloss	din 67 530 (60 DEGREES), GLE	>90
Scratch Resistance	IHD-W466, Method A	1.1N
Abrasion Resistance	Load 1kg, Strokes:20 Steel Wool Type:00	Class1, No changes or visible scratches
Colour Fastness	EN Iso 4892-2, After 200 hXenon - Test	DE <1.7
Surface Protection		A protective PE film

Special Features of Anti Scratch High Gloss Acrylic Panels

1. Anti Scratch High Gloss Acrylic.
2. Available on Premium Grade BWP Russian Birch Plywood.
3. Made in Europe.
4. Robotic and Automated Technology.
5. Warp Free Boards.
6. No Waves, Ripples and Undulations due to Superior Lamination Technology.
7. No Compromise Gloss Boards



Showroom : B-19, Pravasi Industrial Estate, Next to Durian Estate, Off Aarey Road, Goregaon East, Mumbai - 63.

Tel.: 91 22 2927 7377 / 91 22 2927 7007 Mob.: +91 9321576317 / +91 9820064060.

Email: sales@aryamman.in, crm@aryamman.in

www.aryamman.in